



# LAMBERT

## MORTARTITE

**LAMBERT SOUTHWEST**

PO BOX 1111 HENDERSON, TX 75653

(903)657-4680

### Description

MORTARTITE is a blend of Pozzuolanic ash, Stearates, wetting agents and plasticizers. MORTARTITE combines with the free alkali normally in mortar components thus forming water insoluble metallic salts. The use of MORTARTITE will retard the formation of efflorescence and eliminate staining.

#### IMPORTANT FACTS

When MORTARTITE is used in brick mortars, the resultant mix will show:

- a. An increase in compressive strength.
- b. A decrease in the shrinkage to a minimum.
- c. A better wettability of the brick or block thus eliminating hairline cracks and increasing tensile strength between mortar and substrate.
- d. Better working properties and longer working time of the mortar itself.
- e. The wettability of MORTARTITE also will reduce the water ratio by about 25%.

### Directions for Application

MORTARTITE is to be used in the proportion of 1# per sack of cement and 1# per cubic foot of lime or lime putty.

### Packaging

MORTARTITE comes in 50# bags.

**LAMBERT SOUTHWEST**

PO BOX 1111 / 1110 NORTH FRISCO

HENDERSON, TX 75653

(800)-256-8655 or (903)657-4680

Fax (903)657-4805 [www.LambertSW.com](http://www.LambertSW.com)

Lambert Southwest is a division of GW Holladay Interests Inc.

**Distributed By:**